

SP C261SFNw

Color Laser MFP

- Z Copier
- Z Printer
- Z Facsimile
- Z Scanner









Get versatile capabilities at a low cost

If you run a startup or small workgroup, you need a highquality multifunction printer (MFP) that saves you time and offers low long-term costs. The affordable and compact Savin SP C261SFNw Color Laser MFP is designed for personal users or workgroups of up to three people. You'll get jobs moving quickly with print and copy speeds of up to 21 pages per minute (ppm) and easy connectivity from your smartphone or tablet. And with a low TEC value of 1.5 kWh, ENERGY STAR[®] certification and an EPEAT[®] Silver rating, you'll enjoy low energy usage.

Deliver high-impact communications fast

At up to 2400 x 600 dpi resolution, you can still print 21 ppm to deliver documents with vivid color and crisp black text guickly. Plus, the single pass document feeder (SPDF) lets you load up to 50 pages for uninterrupted scanning at up to 40 images per minute (ipm).*

Create a user-friendly workstation

Simplify scan, print, copy and fax jobs with the 4.3" color touchscreen—store up to 12 settings for guick access to common tasks. Load up to three different paper sizes and increase paper capacity to 751 sheets with an optional paper tray to increase efficiency. Plus, with the easy-setup installation wizard, you'll hit the ground running in no time.

*Maximum speed for scanning black-and-white documents. The maximum scan speed for color documents is 24 ipm.

Desktop, Color Laser

System Specifications

Engine Specifications

Configuration/Technology Printing Process Scanning Element Toner Type Color/B&W Print Speed (Letter) Max. Monthly Volume/Duty Cycle First Page Out/Warm Up Time Print Resolution

Electro-photographic printing Flatbed Scanner with full color Contact Image Sensor (CIS) Dry mono-component toner developer, AIO Cartridge 21 ppm Up to 1,500 prints/30,000 prints 14 seconds/30 seconds 600 x 600 dpi (Default) (Speed Mode). 1200 x 600 dpi equivalent (Standard Mode), 2400 x 600 dpi equivalent (Fine Mode) 250-sheet tray + 1-sheet Bypass Tray/ 751 sheets 150 sheets Standard Tray/Bypass Tray: 3.54" x 5.83"–8.5" x 14.0" Standard Tray: 16–43 lb Bond/90 lb, Index (60–160 g/m²) Optional Tray: 16–28 lb. Bond (60–105 g/m²) Duplexing: 16-24 lb. Bond (60-90 g/m2)

Supported Paper Types

Standard/Max Paper Capacity

Standard Output Capacity

Supported Paper Weights

Supported Paper Sizes

Bond*, Cardstock*, Color, Label*, Letterhead, Plain, Pre-printed, Pre-punched, Thick, Thin & Recycled papers, Envelopes* (*via Standard Tray and Bypass only)

Automatic (standard)

63.9 lbs. (29.0 kg)

16.5" x 19.4" x 18.1" (420 x 493 x 460 mm)

Operating: B&W: 331.3 W, Color: 404.1 W,

Duplexing Dimensions (W x D x H) Weight Power Consumption

Sleep Mode: 1.3 W Typical Electricity Consumption (TEC) 1.5 kWh/week Recovery from Sleep Mode 29 seconds 120V, 60Hz, 11A Power Requirements ENERGY STAR Certified EPEAT Silver

Scan Protocols

Facsimile Specifications

Fax Resolution Fax Scanning Speed Modem Speed Fax Compression Method Fax Memory Transmission Speed

LAN-Fax (Outbound TX only), Internet Fax (T.37),

Fax Forwarding to E-Mail/Folder, PSTN, PBX

15.7" x 17.7" x 5.0" (400 x 450 x 127 mm)

Security Features

Standard Fax Features

Wireless LAN Security-WEP, WPA2, Network Security via TCP/IP Access Control, Encrypted Communication using IPsec, IPP Authentication, Locked Print, User Restrictions

500 sheets

8.8 lbs. (4 kg)

2.300 pages*

2,300 pages* 2,300 pages*

2,300 pages*

25,000 pages

Hardware Options Paper Feed Unit TK1220

Paper Capacity: Supported Paper Sizes: Supported Paper Weight: Dimensions (W x D x H): Weight

Consumables and Yields

Print Cartridge Black SP C250A Print Cartridge Cyan SP C250A Print Cartridge Magenta SP C250A Print Cartridge Yellow SP C250A Waster Toner Bottle SP C220

*Declared yield values in accordance with ISO/IEC 19752. Actual yields may vary based on images printed and other factors.

Fixed for 8.5" x 11" / Letter, A4

16-28 lb Bond (60-105 g/m²)

Warranty

The Savin SP C261SFNw is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for period of 90 days from the date of purchase or until depleted, whichever comes first.

Please refer to warranty documents shipped with the product for more details.

www.savin.com

Ricoh USA, Inc., 70 Valley Stream Parkway, Maherm, PA 19355, 1-877-472-8460 @2017 Ricoh USA, Inc., All rights reserved. Savin^{*} and the Savin logo are registered trademarks of Ricoh USA, Inc., Ricoh^{*} and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Savin products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Savin products and services are subject to change from time to time without notice. Products are shown with optional features. Miles are has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will wary depending upon use of the products and services, and the conditions and factors affecting performance. The only warrantie for Savin products and services are as set forth in the express warranty statements accompanying them **\$3890**

600 x 600 dpi (Platen), 300 x 600 dpi (SPDF) Single Pass Document Feeder (SPDF) 50 Sheets 5.5" x 5.5" to 8.5" x 14" (140 x 140 mm to 216 x 356 mm) 14-28 lb. Bond (52-105 g/m²) Platen: Up to 8.5" x 11.7"/A4 (210 x 297 mm), SPDF: Up to 8.5" x 14" (216 x 356 mm) 99 copies 50%, 65%, 78%, 93%, 129%, 155%, 200%, 400% 25% to 400% in 1% increments

10Base-T/100Base-TX, USB 2.0 Type B, USB 2.0 Type A, IEEE802.11b/g/n

Windows Vista, 7, 8.1, 10, Systems Server 2008/R2, Server 2012/R2, Macintosh: OS X 10.9–10.12, Linux and Unix Filter

@Remote, Device Manager NX, Print Driver Packager NX RICOH Smart Device Connector App (for printing only) SP C260 Series Scan App (for scanning only), Apple AirPrint®, Google Cloud Print™, Mopria™

Color and B&W: up to 600 dpi, TWAIN: up to 1200 dpi

Auto Duplex, Combine Copy (2-in-1, 4-in-1), Electronic Sort, ID Card Copy, Image Density, Image Quality Mode (Text, Photo, Mixed), Memory Copy, Auto Tray Switch, Series Copy 400 MHz

256MB RAM

PCL/PS3: 80 fonts

TCP/IP, IPP, Bonjour

PCL6/5c, PostScript 3, PictBridge

Print Specifications Processor Speed

Copy Specifications Copy Resolution

Document Feeder Capacity

Document Feeder Original Size

Document Feeder Paper Weight

Maximum Copy Quantity Reduction & Enlargement Ratios

Document Feeder Type

Maximum Original Size

Copier Features

Zoom Range

Memory (Standard/Maximum) Printer Languages Connection Type Font Support Network Protocols Supported Operating Systems

Device Management Utilities Mobile Printing

Other Print Features

1–999 Set Quantity, Collate, Dithering, Duplexing, Do Not Print Blank Pages, Front Cover, Layout/N-up Printing, Locked Print, Mirror Image Print, Reduce/Enlarge Print, Rotate Print, User Codes, User ID, Watermarks, Economy Color

Up to 8.5" x 11"/A4 Up to 8.5" x 14"

Scan Specifications

Scanner Resolution Scanning Speed (Letter) Platen Size Maximum Scanning Size Scan Modes File Formats Scan-To Modes

Black & White, Grayscale, Color JPEG, Single/Multi Page TIFF, Single/Multi Page PDF Scan-to-Email; Scan-to-Folder (SMB/FTP); Scan-to-Media (USB) TWAIN/WIA, ICA, SANE Scanning Network: TCP/IP; Email: SMTP; Scan-to-Folder: SMB, FTP

B&W: up to 40 ipm, Color: up to 24 ipm

Up to 200 dpi Less than 5 seconds/page (Letter @ 200 dpi) 33.6 kbps with auto fallback MH. MR. MMR. JBIG 100 pages (2.5 MB Flash ROM) Approximately 3 seconds/page *ITU No.1 chart, Compression: MMR, Resolution: Standard speed: 33.6 Kbps 20/200

Quick Dials/ Speed Dials